



**01-350-050 Double Fan, Exhaust 145cfm Wide Plate (19x10)**  
**01-350-070 Double Fan, Intake 145cfm Wide Plate (19x10)**

**Specifications:**

Output: 145 cfm  
Nominal: 0.70A at 12VDC  
Usage: Measured at 10 W  
Connection: Use power supply for standard 110V electrical outlet or use low voltage cable connector with splice for use with ATMOX EZ system or power supply.  
Noise: 34dB  
Mounting: Plate is 19 inches wide by 10 inches high. Mount from inside crawlspace behind existing vent opening.

**Installation:**

Plate is designed to go behind an existing vent opening. Install from inside the crawlspace. Determine where the plate will be mounted. Drill 3-4 holes in the plate wherever screws can be easily mounted to the wall. (Screws are not provided). Connect to power with power supply if using standard outlet or connect to low voltage cable with cable connectors and see installation instructions with power supply or EZ system.

---



**01-350-010 Double Fan, Exhaust 145cfm Plate (14 13/16 x 7 3/8)**  
**01-350-070 Double Fan, Intake 145cfm Plate (14 13/16 x 7 3/8)**

**Specifications:**

Output: 145 cfm  
Nominal: 0.70A at 12VDC  
Usage: Measured at 10 W  
Connection: Use power supply for standard 110V electrical outlet or use low voltage cable connector with splice for use with ATMOX EZ system or power supply.  
Noise: 34dB  
Mounting: Plate is 14 13/16 inches wide by 7 3/8 inches high. Mount from inside crawlspace behind existing vent opening.

**Installation:**

Plate is designed to go behind an existing vent opening. Install from inside the crawlspace. Plate has four holes for screw placement. Mount against wall. (Screws are not provided). Connect to power with power supply if using standard outlet or connect to low voltage cable with cable connectors and see installation instructions with power supply or EZ system.

---



**01-350-015 Double Fan, Exhaust 145cfm with Vent Cover**  
**01-350-035 Double Fan, Intake 145cfm with Vent Cover**

**Specifications:**

Output: 145 cfm  
Nominal: 0.70A at 12VDC  
Usage: Measured at 10 W  
Connection: Use power supply for standard 110V electrical outlet or use low voltage cable connector with splice for use with ATMOX EZ system or power supply.  
Noise: 34dB  
Mounting: Fits standard 8x16 inch vent opening  
Mounts with 4 screws

**Installation:**

Remove existing vent cover, insert the fan and tighten four bolts to hold. Connect to power with power supply if using standard outlet or connect to low voltage cable with cable connectors and see installation instructions with power supply or EZ system.



**01-360-100 Internal Dead Corner – 12VDC Fan**

**Specifications:**

Output: 145 cfm  
Nominal: 0.70A at 12VDC  
Usage: Measured at 10 W  
Connection: Use power supply for standard 110V electrical outlet or use low voltage cable connector with splice for use with ATMOX EZ system or power supply.  
Noise: 34dB  
Mounting: Fits standard 8x16 inch vent opening  
Mounts with 4 screws  
Use: For Residential Use Only

**Installation:**

Attach fan to extension shaft with locknuts and attach extension shaft to mounting bracket. The bracket has holes for screws to be mounted directly to joist in the crawlspace. Generally, fan should blow into or at an angle to the dead space area. Connect to power with power supply if using standard outlet or connect to low voltage cable with cable connectors and see installation instructions with power supply or EZ system.

---

**Limited Two-Year Warranty of ATMOX DC-Powered Fans**

This two-year warranty covers the ATMOX DC-Powered Fans sold by ATMOX INC. The warranty period is for two years from date of invoice.

ATMOX will replace or repair any of the necessary components of the fans that have a manufacturer's defect or are no longer working due to normal wear and tear. The parts will not be covered from any damage caused by acts of God (including lightning strikes and floods), vandalism, electrical surges, fire or other casualty.

ATMOX fans used in conjunction with ATMOX controls are designed to improve conditions in the crawlspace yet are limited by atmospheric conditions.

This warranty does not include any representations regarding mold, insects, termites, water, HVAC or other problems that may occur in a house structure. The warranty does not include any damage or cleanup of the house structure. ATMOX INC'S LIABILITY AS PROVIDED UNDER THIS LIMITED WARRANTY IS STRICTLY LIMITED TO REPAIR OR REPLACEMENT OF THE GOODS.

---

**Contact Information**

ATMOX INC  
10612-D Providence Road #229  
Charlotte, NC 28277

Phone: 704-248-2858  
Email: info@atmox.com

Fax: 704-675-9858  
Website: www.atmox.com